



FORERUNNER



ROADGUIDER

SUPERGUIDER



## QINGDAO QIHANG TYRE CO., LTD.

Factory Add: Mingcun Town, Pingdu City, Qingdao, China

Office Add: Floor 9, No. 29 Capital International Center,

No. 6 Changcheng South RD, Chengyang District,

Qingdao, China

Tel: +86 532 85831197

Fax: +86 532 85831187

Website: [www.qihangtyre.com](http://www.qihangtyre.com)

Mail: [info@qihangtyre.com.cn](mailto:info@qihangtyre.com.cn)



# 2021

QINGDAO QIHANG TYRE CO., LTD.

# CONTENTS

## ABOUT QIHANG 2

## AGRICULTURAL TIRE 3-10

- RADIAL AGRICULTURAL TIRE
- AGRICULTURAL TIRE
- IRRIGATION / PIVOT TIRE
- HARVESTER TIRE

## IMPLEMENT TIRE 11-18

- FARM TIRE
- IMPLEMENT TIRE
- FLOTATION TIRE

## INDUSTRIAL TIRE 19-30

- SKID STEER TIRE
- EXCAVATOR TIRE
- INDUSTRIAL TIRE
- FORKLIFT TIRE
- SOLID TIRE

## OFF THE ROAD TIRE 31-34

- GRADER TIRE
- LOADER TIRE

## TRAILER TIRE 35-40

- RADIAL TRAILER TIRE
- TRAILER TIRE
- MOBILE HOME TIRE
- BOAT TRAILER TIRE
- BIAS LIGHT TRUCK TIRE

## ABOUT QIHANG

Founded in 2000, Qingdao Qihang Tyre CO., Ltd is a tire manufacturer located in Pingdu, Qingdao China. Covering an area of around 130,000 square kilometers, Qihang Tyre employs over 400 staff, who create annual production output worth 500 million RMB.

We supply full line of tires from Industrial, OTR, Agricultural, ST trailer, Lawn and Garden. The diverse portfolio of solutions is offered under several leading brands including **FORERUNNER**, **ROADGUIDER**, **SUPERGUIDER**.

Our quality products pass all the regular testing. DOT, CCC, REACH, and EMARK and meet with ISO9001 standards. We have the state-of-the-art manufacturing and test facilities in the industry. Our premium rubber from Indonesia and Thailand and other raw materials go through the most stringent test. All these combined with our experienced engineers ensure the consistent top quality of our products.

We are always a product driven and customer focused company. Over the years, our quality products and services have helped us build reliable partnerships with our valued customers worldwide.





AGRICULTURAL TIRE

FORERUNNER

600/65R28

600/65R28

600/65R28

# AGRICULTURAL TIRE



## R-1W QH711 RADIAL AGRICULTURAL TIRE

- ▶ Longer service life
- ▶ Excellent stability and comfort
- ▶ Outstanding floating behavior reduces pressure to land

**NEW**

SIZE	TT/TL	LOAD INDEX	SPEED SYMBOLS	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
600/65R28	TL	147/147	A8/B	1491	591	W18L	160	3,075
800/65R32	TL	181/181	A8/B	1853	798	DW25 DW27B DH27B	360	8,250
710/70R38	TL	166/166	A8/B	1959	716	W23	160	5,300
280/85R24	TL	115/112	A8/B	1086	282	W9 W10	160	1,215
320/85R24	TL	122/119	A8/B	1154	319	W9 W10 W11	160	1,500
340/85R28	TL	127/124	A8/B	1188	343	W11 W12	160	1,750
380/85R24	TL	131/128	A8/B	1256	380	W11 W12 W13	160	1,950
380/85R28	TL	133/130	A8/B	1350	389	W12 W13	160	2,060
420/85R28	TL	139/136	A8/B	1425	418	W13	160	2,430
420/85R30	TL	140/137	A8/B	1476	418	W13	160	2,500
420/85R34	TL	142/139	A8/B	1578	418	W13	160	2,650
460/85R30	TL	145/142	A8/B	1527	488	W15L	160	2,900
460/85R34	TL	147/144	A8/B	1649	491	W15L	160	3,075
460/85R38	TL	149/146	A8/B	1750	485	W15L	160	3,250
520/85R38	TL	155/152	A8/B	1857	560	W18L	160	3,875
520/85R42	TL	157/154	A8/B	1969	560	DW18L	160	4,125
380/90R46	TL	149/149	A8/B	1852	380	W12	240	3,250
300/95R46	TL	148/148	A8/B	1717	305	W9	400	3,150



## R-4 QH701 RADIAL AGRICULTURAL TIRE

- ▶ Increase traction performance
- ▶ Enhance shoulder wear and cut resistance performance
- ▶ Enhance tread wear resistance performance

**NEW**

SIZE	TT/TL	LOAD INDEX	SPEED SYMBOLS	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
460/70R24 IND	TL	152/152	A8/B	1254	455	DW14L DW15L DW16L	320	3,550
500/70R24 IND	TL	164/164	A8/B	1310	505	DW15L DW17L	400	5,000



## R-1 QH666 AGRICULTURAL TIRE

- ▶ Excellent traction performance
- ▶ Better self-cleaning capability
- ▶ Excellent stability and comfort

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
12.4-24	8PR	TT	1,159	315	W11	220	1,285
12.4-24	12PR	TT	1,159	315	W11	330	1,600
12.4-36	8PR	TT	1,464	315	W11	220	1,500
12.4-36	12PR	TT	1,464	315	W11	330	1,850
12.4-38	8PR	TT	1,514	315	W11	220	1,600
12.4-38	12PR	TT	1,514	315	W11	320	1,850
14.9-24	8PR	TT	1,265	378	W13	180	1,600
14.9-24	12PR	TT	1,265	378	W13	260	2,000
14.9-28	8PR	TT	1,367	378	W13	180	1,700
14.9-28	12PR	TT	1,367	378	W13	250	1,950
15.5-38	10PR	TT	1,569	394	W14L	220	2,000
15.5-38	12PR	TT	1,569	394	W14L	260	2,120
16.9-30	10PR	TT	1,485	429	W15L	190	2,240
16.9-30	12PR	TT	1,485	429	W15L	230	2,500
18.4-30	10PR	TT	1,552	467	W16L	180	2,500
18.4-30	12PR	TT	1,552	467	W16L	220	2,900
18.4-34	10PR	TT	1,654	467	W16L	180	2,725
18.4-34	12PR	TT	1,654	467	W16L	220	3,000
18.4-38	10PR	TT	1,755	467	W16L	180	2,900
18.4-38	12PR	TT	1,755	467	W16L	220	3,250
18.4-42	10PR	TT	1,857	467	W16L	180	3,000
18.4-42	12PR	TT	1,857	467	W16L	220	3,350
20.8-38	10PR	TT	1,834	528	W18L	150	3,150
20.8-38	12PR	TT	1,834	528	W18L	190	3,550
24.5-32	12PR	TT	1,803	622	DW21A	170	4,000
24.5-32	16PR	TT	1,803	622	DW21A	210	4,500
30.5L-32	18PR	TL	1,845	775	DW27	220	5,800

# AGRICULTURAL TIRE



## R-1 QH611 AGRICULTURAL TIRE

- ▶ Excellent grip ability
- ▶ Increase traction performance

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
<b>NEW</b> 757X176-12	6PR	TT	610	170	4.5E	250	405
4.00-12	4PR	TT	535	112	3.00D	240	280
5.00-12	6PR	TT	590	145	4.00E	200	280
6.00-12	6PR	TT	635	152	4.50E	250	405
6.00-14	8PR	TT	690	165	4.50E	250	600
6.00-16	8PR	TT	690	165	4.50E	250	495
6.50-16	8PR	TT	765	180	4.50E	250	565
7.50-16	8PR	TT	810	205	5.50F	210	650
7.50-20	8PR	TT	910	205	5.50F	240	760
8.3-16	6PR	TT	790	211	W7	230	695
8.3-20	8PR	TT	788	211	W7	240	695
8.3-24	8PR	TT	993	211	W7	240	810
9.5-20	8PR	TT	950	240	W8	210	955
9.5-24	8PR	TT	1,048	241	W8	210	940
11.2-24	8PR	TT	1,103	284	W10	250	1,150
<b>NEW</b> 11-32	8PR	TT	1,360	305	W10	200	1,230
<b>NEW</b> 11-32	12PR	TT	1,360	305	W10	290	1,530
11.2-38	8PR	TT	1,459	284	W10	180	1,150
12.4-24	8PR	TT	1,159	315	W11	220	1,285
12.4-24	12PR	TT	1,159	315	W11	330	1,600
13.6-20	8PR	TT	980	295	W8L	230	935
13.6-20	10PR	TT	980	295	W8L	280	975
13.6-24	8PR	TT	1,210	345	W12	190	1,400
13.6-24	12PR	TT	1,210	345	W12	260	1,600
13.6-28	8PR	TT	1,311	345	W12	190	1,500
13.6-28	12PR	TT	1,311	345	W12	290	1,900
13.6-38	8PR	TT	1,565	345	W12	210	1,750
13.6-38	12PR	TT	1,565	345	W12	260	2,000
14.9-24	8PR	TT	1,265	378	W13	180	1,600
14.9-24	12PR	TT	1,265	378	W13	260	2,000

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
14.9-26	8PR	TT	1,316	378	W13	190	1,650
14.9-26	12PR	TT	1,316	378	W13	260	2,060
14.9-30	8PR	TT	1,415	378	W13	180	1,940
14.9-30	10PR	TT	1,415	378	W13	230	2,190
<b>NEW</b> 15-24	10PR	TT	1,330	410	DW14	280	2,800
<b>NEW</b> 15-24	12PR	TT	1,330	410	DW14	320	3,020
15.5-38	10PR	TT	1,569	394	W14L	220	2,000
15.5-38	12PR	TT	1,569	394	W14L	260	2,120
16.9-24	10PR	TT	1,333	429	W15L	190	2,000
16.9-24	12PR	TT	1,333	429	W15L	230	2,120
16.9-28	10PR	TT	1,435	429	W15L	190	2,120
16.9-28	12PR	TT	1,435	429	W15L	230	2,360
16.9-30	10PR	TT	1,485	429	W15L	190	2,240
16.9-30	12PR	TT	1,485	429	W15L	230	2,500
16.9-34	10PR	TT	1,587	429	W15L	190	2,360
16.9-34	12PR	TT	1,587	429	W15L	230	2,575
18.4-26	12PR	TT	1,450	467	DW16	220	2,650
18.4-26	14PR	TT	1,450	467	DW16	250	2,800
18.4-30	10PR	TT	1,552	467	W16L	180	2,500
18.4-30	12PR	TT	1,552	467	W16L	220	2,900
18.4-34	10PR	TT	1,654	467	W16L	180	2,725
18.4-34	12PR	TT	1,654	467	W16L	220	3,000
18.4-38	10PR	TT	1,755	467	W16L	180	2,900
18.4-38	12PR	TT	1,755	467	W16L	220	3,250
20.8-38	10PR	TT	1,834	528	W18L	150	3,150
20.8-38	12PR	TT	1,834	528	W18L	190	3,550
23.1-26	12PR	TT	1,605	587	DW20	170	3,250
23.1-26	16PR	TT	1,605	587	DW20	220	3,750
23.1-30	12PR	TT	1,707	587	DW20	170	3,450
23.1-30	16PR	TT	1,707	587	DW20	225	4,000

# AGRICULTURAL TIRE



## R-1 QH612 AGRICULTURAL TIRE

- ▶ Excellent self-cleaning features and traction performance

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
14.9-28	8PR	TT	1,367	378	W13	180	1,700
14.9-28	12PR	TT	1,367	378	W13	250	1,950



## R-1 QH777 AGRICULTURAL TIRE

- ▶ Exceptional load capacity
- ▶ Better soil protection

**NEW**

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
13.6-24	8PR	TT	1,210	345	W12	210	1,545
13.6-24	10PR	TT	1,210	345	W12	250	1,790
14.9-26	10PR	TT	1,315	378	W13	230	2,055
14.9-26	12PR	TT	1,315	378	W13	260	2,090
16.9-34	10PR	TT	1,585	430	W15L	200	2,605
16.9-34	12PR	TT	1,585	430	W15L	230	2,820
18.4-38	10PR	TT	1,755	467	W16L	180	3,165
18.4-38	12PR	TT	1,755	467	W16L	230	3,575



## R-1 QH615 AGRICULTURAL TIRE

- ▶ More efficient traction and puncture resistant

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
11.2-28	6PR	TT	1,205	284	W10	180	1,000
11.2-28	8PR	TT	1,205	284	W10	250	1,180
12.4-28	8PR	TT	1,260	315	W11	220	1,400
12.4-28	12PR	TT	1,260	315	W11	330	1,650



## R-2 QH651 AGRICULTURAL TIRE

- ▶ Higher strength and durability
- ▶ Wear and puncture resistance
- ▶ Good grip and self-cleaning performance

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
<b>NEW</b> 9.5-24	8PR	TT	1120	285	W8	280	1,100
12.4-24	8PR	TT	1,192	315	W11	220	1,285
<b>NEW</b> 13.6-24	10PR	TT	1210	350	W12	250	1,910
14.9-24	8PR	TT	1,305	378	W13	180	1,600
14.9-28	8PR	TT	1,406	378	W13	180	1,700
18.4-30	10PR	TT	1,550	467	W16L	180	2,500
18.4-34	10PR	TT	1,655	467	W16L	180	2,725
18.4-38	10PR	TT	1,755	467	W16L	180	2,900
<b>NEW</b> 20.8-38	12PR	TT	1,887	528	W18L	200	4,000
23.1-26	16PR	TT	1,605	587	DW20	220	3,750
23.1-30	16PR	TT	1,829	610	DW20	225	4,000
<b>NEW</b> 23.1-34	12PR	TT	1,850	590	DW20A	225	4,500
<b>NEW</b> 24.5-32	16PR	TT	1,862	622	DW21	140	3,560



## R-1 QH616 IRRIGATION / PIVOT TIRE

- ▶ Better soil protection and excellent stability

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
11.2-38	6PR	TT/TL	1,420	260	W10	180	1,150
14.9-24	6PR	TT/TL	1,265	378	W13	140	1,360

# IMPLEMENT TIRE



# IMPLEMENT TIRE



## F-2 QH621 FARM TIRE

- ▶ Lateral grip and wear resistance
- ▶ Good traction performance
- ▶ Protection against cuts and lateral lacerations

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
4.00-12	4PR	TT/TL	535	110	3.00D	340	250
4.00-19	4PR	TT/TL	720	110	3.00D	360	325
5.00-15	4PR	TT/TL	665	140	4J	300	325
5.00-16	6PR	TT/TL	665	150	4.00E	390	475
5.50-16	8PR	TT/TL	710	150	4.00E	370	530
6.00-16	8PR	TT/TL	740	160	4.00E	450	675
6.50-16	8PR	TT/TL	750	175	4.50E	420	735
7.5L-15	8PR	TT/TL	745	208	6LB	330	750
7.50-16	8PR	TT/TL	810	205	5.50F	390	775
7.50-18	8PR	TT/TL	860	205	5.50F	390	850
7.50-20	8PR	TT/TL	910	205	5.50F	370	1,020
9.5L-15	8PR	TT/TL	780	240	8LB	330	850
11L-15	8PR	TT/TL	810	280	8LB	300	950
9.00-16	8PR	TT/TL	890	245	W7L	400	1,200
10.00-16	10PR	TT/TL	910	275	W8L	360	1,120
11.00-16	12PR	TT/TL	970	315	W10L	410	1,550



## F-2 QH622 FARM TIRE

- ▶ Better weight distribution, contributing to lower soil compaction
- ▶ High load capacity
- ▶ Greater resistance to impacts, cuts and lacerations

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
10.00-16	10PR	TT/TL	910	275	W8L	360	1,120
11.00-16	12PR	TT/TL	970	315	W10L	410	1,550



## F-2 QH623 FARM TIRE

- ▶ Small rotation resistance, flexible turn control
- ▶ Small rolling resistance
- ▶ Good self-cleaning performance

**NEW**

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
7.50-16	8PR	TT/TL	810	205	5.50F	390	775



## F-2 QH624 FARM TIRE

- ▶ Small rotation resistance, flexible turn control
- ▶ Good self-cleaning performance

**NEW**

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
7.50-16	8PR	TT/TL	810	205	5.50F	390	775



## I-2 QH626 IMPLEMENT TIRE

- ▶ Small rotation resistance, flexible turn control
- ▶ Good self-cleaning performance

**NEW**

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
10.0/75-15.3	10PR	TT	880	285	9.00	390	1,525
10.0/75-15.3	12PR	TT	880	285	9.00	430	1,800



## I-1 QH628 IMPLEMENT TIRE

- ▶ Minimal soil embossing and excellent load distribution
- ▶ Greater resistance to impacts, cuts and lacerations

**NEW**

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
10-15 (10.00-15)	10PR	TT	748	260	W9	340	1,035
10-15 (10.00-15)	12PR	TT	748	260	W9	410	1,250



# IMPLEMENT TIRE



## F-3 QH631 FARM TIRE

- ▶ Good wear resistance
- ▶ Ensures excellent stability and drivability

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
11L-15	10PR	TL	813	279	8LB	360	1,060
11L-16	12PR	TL	838	279	8LB	440	1,250



## F-3 QH632 FARM TIRE

- ▶ Superior grip and sel-cleaning capacity
- ▶ Good aging and wearing resistance

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
11L-16	12PR	TL	838	279	8LB	440	1,250



## F-3 QH633 FARM TIRE

- ▶ Excellent stability and drivability
- ▶ Good aging and wearing resistance

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
<b>NEW</b> 400/60-15.5	14PR	TL	874	400	13	360	2,900
11L-16	12PR	TL	838	279	8LB	440	1,250
<b>NEW</b> 500/50-17	16PR	TL	940	505	16	400	3,550



## QH638 IMPLEMENT TIRE

- ▶ High Speed,High load capacity
- ▶ Small rolling resistance

**NEW**

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
16.5/70-18	18PR	TTF	1,045	418	13.00	590	4,250



## I-1 QH311 IMPLEMENT TIRE

- ▶ Directional and self-clean out tread design for improved traction performance
- ▶ Good heat dissipation

**NEW**

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
10.0/80-12	12PR	TL	710	264	9.0	440	1,500
10.0/75-15.3	18PR	TL	760	264	9.0	550	1,900



## I-1 QH641 IMPLEMENT TIRE

- ▶ Minimal soil embossing and excellent load distribution
- ▶ Greater resistance to impacts,cuts and lacerations
- ▶ Prevents punctures and tire corrosion

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
6.50-16	10PR	TT/TL	735	173	4.50E	410	920
7.50-16	10PR	TT/TL	788	211	5.50F	410	1,215
7.60L-15	8PR	TT/TL	734	193	5.5	360	950
9.5L-14	8PR	TT/TL	741	241	7.0	300	1,090
9.5L-15	8PR	TT/TL	780	240	8LB	300	1,120
9.00-16	10PR	TT/TL	848	234	6LB	360	1,500
10.5/80-18	10PR	TT/TL	885	276	9.0	410	1,550
11L-14	8PR	TT/TL	750	280	8LB	250	1,120
11L-15	12PR	TT/TL	810	280	8LB	360	1,450
11L-16	12PR	TT/TL	835	280	8LB	360	1,500
12.5L-15	12PR	TT/TL	823	318	10.0	360	1,750



## I-1 QH642 IMPLEMENT TIRE ( HIGHWAY USE )

- ▶ Designed for site transport and road transport
- ▶ The soil in the fields is reduced and the damage to crops is avoided

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
9.5L-15	12PR	TT/TL	741	241	7LB	620	1,550
11L-15	12PR	TT/TL	810	280	8LB	620	1,800
12.5L-15	12PR	TT/TL	823	318	10.0	620	2,120

# IMPLEMENT TIRE



## I-3 QH643 FLOTATION TIRE

- ▶ Wear and puncture resistance
- ▶ Good grip and self-cleaning performance
- ▶ Better distribution of load to withstand high loads

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
400/60-15.5	14PR	TL	874	400	13	360	2,900
500/50-15.5	14PR	TL	874	500	17	390	3,150
500/50-17	18PR	TL	950	500	16	480	4,125
400/55-22.5	16PR	TL	1,020	405	AG 11.75	400	3,550
400/60-22.5	16PR	TL	1,070	400	13.00	350	4,000
500/45-22.5	16PR	TL	1,045	500	16.00	360	3,750
500/60-22.5	16PR	TL	1,170	500	16.00	320	4,875
550/45-22.5	16PR	TL	1,070	550	16.00	280	4,375
550/60-22.5	16PR	TL	1,238	550	16	280	5,450
600/50-22.5	16PR	TL	1,170	610	20	260	5,150
600/55-22.5	16PR	TL	1,238	600	16	280	5,600
700/40-22.5	16PR	TL	1,170	700	24.00	220	5,300
700/50-22.5	16PR	TL	1,270	700	24.00	240	6,700
600/55-26.5	16PR	TL	1,354	600	AG 20.00	260	6,000
700/50-26.5	16PR	TL	1,354	700	24.00	240	6,700
800/45-26.5	16PR	TL	1,354	800	28.00	220	7,300
650/65-30.5	16PR	TL	1,650	650	20.00	220	7,750
750/60-30.5	16PR	TL	1,650	750	24.00	220	8,500
850/50-30.5	16PR	TL	1,650	850	28.00	220	9,500



## I-3 QH645 IMPLEMENT TIRE

- ▶ Greater resistance to impacts, cuts and lacerations
- ▶ Good self-cleaning performance

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
<b>NEW</b> 26x12.00-12	8PR	TL	648	307	10.50I	340	1,370
<b>NEW</b> 29x12.50-15	8PR	TL	730	320	10 LB	310	1,080
31x15.5-15	8PR	TL	792	391	13.00	310	1,250



## QH671 IMPLEMENT TIRE

- ▶ Tear-resistance and cracking resistance
- ▶ Lateral grip and self-cleaning performance

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
6.50-16	10PR	TT	760	165	4.50E	410	1,010



## QH672 IMPLEMENT TIRE

- ▶ Good tread flexibility
- ▶ Good cut resistance
- ▶ Good puncture resistance

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
7.00-16	12PR	TT	790	176	5.50	410	1,335



## IMP700 IMPLEMENT TIRE

- ▶ High load capacity
- ▶ Reduce soil compaction
- ▶ Good heat dissipation

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
10.0/80-12	12PR	TL	710	264	9.0	440	1,500
10.0/75-15.3	12PR	TL	760	264	9.0	470	1,700
11.5/80-15.3	12PR	TL	865	290	9.0	410	2,145
12.5/80-15.3	14PR	TL	875	307	9.0	410	2,385
<b>NEW</b> 10.5/65-16	10PR	TL	755	274	11.00	520	1,550
<b>NEW</b> 13.0/55-16	14PR	TL	763	343	11.00	520	2,240
<b>NEW</b> 15.0/55-17	16PR	TL	850	391	13.00	570	3,320
<b>NEW</b> 19.0/55-17	16PR	TL	864	490	16.00	420	3,930
<b>NEW</b> 13.0/65-18	14PR	TL	890	336	11.00	450	2,555

# INDUSTRIAL TIRE



# INDUSTRIAL TIRE



## SKS-1 SKID STEER TIRE

- ▶ Thicker sidewall and larger rim guard for superior durability
- ▶ Directional and self-clean out tread design for an improved traction performance
- ▶ Classic tread pattern suitable for the most popular use

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
10.0/75-15.3	12PR	TL	760	264	9.00	425	1,700
11L-16	12PR	TL	838	279	8.00	440	1,250
10-16.5	10PR	TL	779	261	8.25	520	2,135
12-16.5	12PR	TL	830	312	9.75	550	2,865
14-17.5	14PR	TL	922	351	10.50	550	3,875
15-19.5	14PR	TL	1,029	391	11.75	485	4,565



## SKS-2 SKID STEER TIRE

- ▶ Multi-angled and bold lug-bars, deep tread and extra thick sidewall
- ▶ Excellent wear-resistance and puncture resistance for longer service durability
- ▶ Tread contact patch with broader lugs for heavy duty prime-movers

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
10-16.5	12PR	TL	773	264	8.25	620	2,375
12-16.5	14PR	TL	835	307	9.75	620	3,075



## SKS-3 SKID STEER TIRE

- ▶ The high contact rate between the surface and the tread pattern depth, provides super resistance to wear and puncture
- ▶ The aggressive tread pattern provides good traction and excellent handling
- ▶ Designed to give high stability to the machine and it is particularly recommended on challenging terrains

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
10-16.5	12PR	TL	773	264	8.25	620	2,375
12-16.5	14PR	TL	831	307	9.75	620	3,075



## SKS-4 SKID STEER TIRE

- ▶ Broadest contact surface and maximum gripping power
- ▶ Cut and chip resistance, longer tread life
- ▶ block pattern tire for skid steers, suitable for heavy-duty service

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
10-16.5	12PR	TL	773	264	8.25	620	2,375
12-16.5	14PR	TL	831	325	9.75	620	3,075



## SKS-5 SKID STEER TIRE

- ▶ Thicker sidewall and larger rim guard for superior durability
- ▶ Directional and self-cleanout tread design for an improved traction performance
- ▶ Classic tread pattern suitable for the most popular use

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
23*8.5-12	6PR	TL	574	213	7.00	340	820
27*8.5-15	6PR	TL	678	213	7.00	340	710
27*10.5-15	6PR	TL	691	259	8.50	340	750
10-16.5	10PR	TL	775	264	8.25	520	2,135
12-16.5	12PR	TL	831	320	9.75	550	2,865



## SKS-6 SKID STEER TIRE

- ▶ Newly designed tread pattern creates extended wear for high abuse and hard surface applications
- ▶ The extra deep tread with wider and sturdier blocks provides best traction, stability, and puncture resistance
- ▶ Longer service life resulting in reduced cost per hour

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
10-16.5	12PR	TL	795	264	8.25	620	2,375
12-16.5	14PR	TL	831	315	9.75	620	3,075

# INDUSTRIAL TIRE



## SKS-7 SKID STEER TIRE

- ▶ Greater stability and puncture resistance through heavy duty sidewall and more depth lugs
- ▶ Heavier ply ratings for severe construction sites
- ▶ Suitable for heavy-duty service

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
10-16.5	12PR	TL	795	264	8.25	620	2,375
12-16.5	14PR	TL	835	307	9.75	620	3,075



## SKS-8 SKID STEER TIRE

- ▶ Wide section width and largest lugs give optimum traction and increase the stability and prolong the tread life
- ▶ Full ply and robust construction reduces the risk of damage
- ▶ Excellent abrasion resistance with modern design

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
10-16.5	10PR	TL	779	261	8.25	520	2,135
12-16.5	12PR	TL	830	312	9.75	550	2,865



## QH107 EXCAVATOR TIRE

- ▶ Sidewall protection.
- ▶ Resistance to lateral skidding.
- ▶ Deep grooves offer the excellent abrasion resistance.

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
8.25-20	14PR	TTF	992	245	6.50	720	2,240
9.00-20	14PR	TTF	1,030	260	7.00	770	2,575
10.00-20	16PR	TTF	1,062	280	7.50	810	3,000



## QH108 EXCAVATOR TIRE (SUPER DEEP TREAD)

- ▶ Extra deep tread and more lugs ensuring an extended tire life-cycle
- ▶ The best traction and outstanding self-cleaning features
- ▶ Strong body and high loading suitable to heavy-duty service

**NEW**

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
9.00-20	18PR	TTF	1,020	260	7.00	760	4,000



## R-4 QH601 INDUSTRIAL TRACTOR TIRE

- ▶ The tread pattern has directionality and suitable for soft soil, mud land and sand
- ▶ The pattern is self-cleaning and has excellent traction performance
- ▶ Strong sidewall structure

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
16.9-24	12PR	TL	1,236	429	DW15	260	3,250
16.9-28	12PR	TL	1,435	430	DW15	260	3,450
18.4-26	12PR	TL	1,426	467	DW16A	250	3,875
17.5L-24	12PR	TL	1,241	445	DW15L	260	3,000
19.5L-24	12PR	TL	1,314	495	DW17L	230	3,450
21L-24	12PR	TL	1,402	533	DW18A	220	3,875



## R-4 QH602 INDUSTRIAL TRACTOR TIRE

- ▶ Great traction on drive wheels providing the best performance on and off the road
- ▶ The extra deep tread with wider and larger lugs
- ▶ Best traction, stability and puncture resistance

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
10.0/75-15.3	10PR	TL	760	264	9.0	390	1,525
11.5/80-15.3	12PR	TL	865	290	9.0	410	2,145
<b>NEW</b> 305/80-16(20.5/70-16)	14PR	TL	950	265	10.00	280	1,600
15.5/80-24	12PR	TL	1,280	378	W13	300	2,900

# INDUSTRIAL TIRE



## R-4 QH603 ALL TRACTOR UTILITY TIRE

- ▶ The tread pattern has directionality and is suitable for soft soil, mud land and sand
- ▶ The pattern is self-cleaning and has excellent traction performance
- ▶ Strong sidewall structure

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
10.5/80-18	10PR	TL	912	274	9.0	370	1,935
12.5/80-18	12PR	TL	1,001	350	9.0	370	2,625



## R-4 QH604 ALL TRACTOR UTILITY TIRE

- ▶ Modern design
- ▶ Much larger lugs, the force area is large, ensures good stability and higher durability
- ▶ Strong sidewall structure

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
12.5/80-18	12PR	TL	1,001	350	9.0	370	2,625



## R-4 QH605 INDUSTRIAL TRACTOR TIRE

- ▶ The sidewall protection features particular resistance against cuts and bruises
- ▶ Broadest contact surface and maximum gripping power
- ▶ longer life even on hard surfaces in addition to excellent stability

**NEW**

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
12.5/80-18	12PR	TL	1,015	308	9.0	370	2,650
16.9-28	14PR	TL	1,435	430	DW15	300	3,765



## R-4 QH606 INDUSTRIAL TRACTOR TIRE

- ▶ Good traction and excellent handling
- ▶ Good traction performance

**NEW**

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
8.25-16	16PR	TT	845	220	5.50F	730	1,800



## R-4 QH607 INDUSTRIAL TRACTOR TIRE

- ▶ The tread pattern has directionality and suitable for soft soil, mud land and sand
- ▶ The pattern is self-cleaning and has excellent traction performance
- ▶ Strong sidewall structure

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
19.5L-24	12PR	TL	1,314	495	DW16A	230	3,455



## L-5 QH608L INDUSTRIAL TIRE (HEAVY DUTY USE)

- ▶ The tread with wider and larger lugs providing best traction, stability and puncture resistance
- ▶ The force area is large, ensures the stability and excellent wear resistance
- ▶ Strong sidewall structure

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
19.5L-24	12PR	TL	1,314	495	DW17L	230	3,455



## L-5 QH608 INDUSTRIAL TIRE (HEAVY DUTY USE-SUPER DEEP TREAD)

- ▶ It has a super-strong tyre body, lengthened tread of tyre and high-strength and high-hardness special tread formula, so that it has good cutting resistance, puncture resistance and wear resistance
- ▶ Due to the special running area and pattern design, the running stability and the passing performance are good

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
12.5/80-18	14PR	TL	1,001	350	9.0	370	2,625
16.9-24	12PR	TL	1,309	429	W15L	260	3,240
16.9-28	12PR	TL	1,435	430	DW15	260	3,450
19.5L-24	12PR	TL	1,314	495	DW17L	230	3,455

**NEW**  
**NEW**  
**NEW**

# INDUSTRIAL TIRE



## R-4 QH609 INDUSTRIAL TRACTOR TIRE

- ▶ More lugs for improved puncture resistance
- ▶ better durability provided by the natural shaped carcass
- ▶ Strong sidewall structure

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
19.5L-24	12PR	TL	1,314	495	DW17L	230	3,455



## QH880 INDUSTRIAL TRACTOR TIRE

- ▶ This pattern is applicable for various engineering machinery vehicles and has wide running area and deep patterns
- ▶ It has good towing property, wear resistance and cut resistance, long service life and tight tyre body
- ▶ It is little deformed and can be renewed for many times

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
405/70-20	14PR	TL	1,076	407	13.0	390	3,250
405/70-24	14PR	TL	1,178	407	13.0	390	3,550



## QH201 FORKLIFT TIRE

- ▶ Suitable for scrapers and forklifts in areas like ports, factories, warehouse, etc.
- ▶ With excellent cutting and wearing resistance
- ▶ Good contact and traction performance provided by thick tread pattern

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
4.00-8	10PR	TTF	422	108	2.50	1,000	745
5.00-8	10PR	TTF	469	131	3.00	1,000	1,090
6.00-9	10PR	TTF	540	160	4.00	860	1,505
6.50-10	12PR	TTF	590	178	5.00	970	1,655
7.00-9	10PR	TTF	590	190	5.00	860	1,995
7.00-12	14PR	TTF	676	192	5.00	860	2,060
7.00-15(29x8-15)	12PR	TTF	760	199	5.50	860	2,500
7.50-15	12PR	TTF	798	215	6.00	790	2,600
8.15-15(28x9-15)	14PR	TTF	684	221	7.00	970	3,075
8.25-12	12PR	TTF	728	210	6.50	720	3,060
8.25-15	14PR	TTF	834	236	6.50	720	3,775
18X7-8	14PR	TTF	465	168	4.33	900	1,450



## QH202 FORKLIFT TIRE

- ▶ Designed for forklift equipment in material handling and industrial applications
- ▶ Strong structure offers low rolling resistance, lower vibration, and greater stability as well as increased puncture resistance
- ▶ Exceptional cut and chip resistance along with excellent wear resistance

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
10.00-20	16PR	TTF	1,055	278	7.50	790	6,765
12.00-20	20PR	TTF	1,125	315	8.50	965	8,970



## QH207 FORKLIFT TIRE (ECONOMICAL)

- ▶ Suitable for scrapers and forklifts in areas like factories, warehouse
- ▶ Good contact and traction performance provided by thick tread pattern

**NEW**

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
6.00-9	10PR	TTF	540	160	4.00	860	1,505
6.50-10	12PR	TTF	590	178	5.00	970	1,655
7.00-12	12PR	TTF	676	192	5.00	860	2,060
8.15-15(28x9-15)	14PR	TTF	684	221	7.00	970	3,075



## QH208 FORKLIFT TIRE (SUPER DEEP TREAD)

- ▶ Suitable for scrapers and forklifts in areas like ports, factories, warehouse
- ▶ With excellent cutting and wearing resistance

**NEW**

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
6.00-9	10PR	TTF	540	160	4.00	860	1,505
6.50-10	12PR	TTF	590	178	5.00	970	1,655
7.00-12	12PR	TTF	676	192	5.00	860	2,060
8.25-15	14PR	TTF	834	236	6.50	720	3,775

# INDUSTRIAL TIRE

## QH301/QH302

### PRESS ON SOLID TIRE



- ▶ Super strong press-on solid tire
- ▶ Special compounds improving load capacity and resistance to puncture, extend service life
- ▶ Wide footprint for maximum grip and lifting stability

SIZE	(mm)	MAX LOAD (kg)					
		COUNTERBALANCED LIFT TRUCK				OTHER INDUSTRIAL 16KM/H	
		10KM/H		16KM/H			
		LOAD (kg)	ROTATION (mm)	LOAD (kg)	ROTATION (mm)		
9x5x5	229x127x127	890	790	850	785	680	
10-5x6 1/2	254x127x165.1	940	850	910	840	730	
14x4 1/2x8	356x114x203.2	1,090	965	1,040	960	960	
15 1/2x6x10	394x152x254	1,735	1,540	1,660	1,535	1,335	
16x5x10 1/2	406x127x266.7	1,400	1,250	1,340	1,240	1,080	
16x6x10 1/2	406x152x266.7	1,780	1,580	1,700	1,570	1,370	
16 1/4x5x11 1/4	413x127x285.8	1,415	1,260	1,350	1,250	1,090	
16 1/4x6x11 1/4	413x152x285.8	1,780	1,580	1,710	1,580	1,370	
18x6x12 1/8	457x152x308	1,950	1,740	1,860	1,720	1,500	
18x7x12 1/8	457x178x308	2,370	2,110	2,270	2,100	1,820	
18x8x12 1/8	457x203x308	2,790	2,480	2,670	2,470	2,150	
21x6x15	533x152x381	2,280	2,020	2,160	2,000	1,740	
21x7x15	533x178x381	2,670	2,380	2,550	2,360	2,050	
21x8x15	533x203x381	3,110	2,795	3,000	2,780	2,420	
22x9x16	559x229x406.4	3,750	3,340	3,590	3,320	2,890	
22x12x16	599x305x406.4	5,235	4,660	5,000	4,630	4,030	



## QH303/QH304

### PNEUMATICS SHAPED SOLID TIRE



- ▶ Super strong pneumatic shaped solid tire
- ▶ Special compounds improving load capacity and resistance to puncture, extend service life
- ▶ Deep tread configuration for superior traction

SIZE	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	MAX LOAD(kg)				
				COUNTERBALANCED LIFT TRUCK				OTHER INDUSTRIAL 16KM/H
				10KM/H		25KM/H		
				LOAD (kg)	ROTATION (mm)	LOAD (kg)	ROTATION (mm)	
5.00-8	469	126	3.00	1,210	970	1,175	880	840
6.00-9	545	140	4.00	1,920	1,535	1,855	1,390	1,325
6.50-10	597	157	5.00	2,640	2,110	2,545	1,910	1,820
7.00-9	578	170	5.00	2,730	2,015	2,606	1,925	1,940
7.00-12	683	168	5.00	3,015	2,410	2,910	2,185	2,075
7.00-15	759	178	5.50	3,590	2,870	3,460	2,600	2,475
8.25-12	735	206	5.00	3,325	2,660	3,210	2,410	2,295
8.25-15	847	205	6.50	4,940	3,950	4,765	3,575	3,405
16x6-8	418	156	4.33	1,500	1,200	1,445	1,085	1,035
18x7-8	457	165	4.33	2,350	1,880	2,265	1,700	1,620
21x8-9	535	189	6.00	2,810	2,250	2,715	2,035	1,940
23x9-10	200	595	6.50	3,420	2,735	3,300	2,475	2,355
27x10-12	683	236	8.00	4,465	3,570	4,315	3,235	3,080
28x9-15	700	230	7.00	4,090	3,270	3,945	2,960	2,820
250-15	734	226	7.00	4,675	3,740	4,515	3,385	3,225



# OTR TIRE



# OFF THE ROAD TIRE



## G2/L2 QH807 GRADER TIRE

- ▶ This pattern is applicable for various engineering machinery vehicles and has wide running area and deep patterns
- ▶ It has good towing property, wear resistance and cut resistance, long service life and tight tyre body
- ▶ It is little deformed and can be renewed for many times

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
15.5-25	12PR	TL	1,275	395	12.00/1.3	250	2,650
17.5-25	12PR	TL	1,350	445	14.00/1.5	200	2,900
17.5-25	16PR	TL	1,350	445	14.00/1.5	280	3,350
20.5-25	16PR	TL	1,490	520	17.00/2.0	225	4,000



## G2/L2 QH808 GRADER TIRE

- ▶ This pattern is applicable for various engineering machinery vehicles and has wide running area and deep patterns
- ▶ It has good towing property, wear resistance and cut resistance, long service life and tight tyre body
- ▶ It is little deformed and can be renewed for many times

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
13.00-24	12PR	TL	1,280	330	8.00TG	300	2,725
13.00-24	16PR	TL	1,280	330	8.00TG	325	3,075
14.00-24	12PR	TL	1,350	360	8.00TG	250	3,075
14.00-24	16PR	TL	1,350	360	8.00TG	350	3,650
15.5-25	12PR	TL	1,275	395	12.00/1.3	250	2,650
17.5-25	12PR	TL	1,350	445	14.00/1.5	200	2,900
17.5-25	16PR	TL	1,350	445	14.00/1.5	280	3,350
20.5-25	16PR	TL	1,490	520	17.00/2.0	225	4,000
23.5-25	16PR	TL	1,615	595	19.00/2.5	200	4,750



## G2/L2 QH809 GRADER TIRE

- ▶ It is suitable for all kinds of construction machinery vehicles based on wide driving surface, deep pattern, good traction performance, wear resistance and cutting resistance
- ▶ Longer service life, solid matrix, small deformation and can be repeatedly renovated

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
14.00-24	12PR	TL	1,350	360	8.00TG	250	3,075
14.00-24	16PR	TL	1,350	360	8.00TG	350	3,650



## E3/L3 QH811 LOADER TIRE

- ▶ This pattern is applicable for various engineering machinery vehicles and has wide running area and deep patterns
- ▶ It has good towing property, wear resistance and cut resistance, long service life and tight tyre body
- ▶ It is little deformed and can be renewed for many times

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
<b>NEW</b> 20.5/70-16	16PR	TL/TTF	920	340	10.00F	280	1,600
16/70-20	16PR	TL/TTF	1,067	410	13.00	350	2,600
16/70-24	16PR	TL/TTF	1,175	410	13.00	350	3,350
14.00-24	16PR	TL/TTF	1,370	375	11.00	375	4,000
15.5-25	12PR	TL/TTF	1,275	395	12.00/1.3	250	3,250
17.5-25	16PR	TL/TTF	1,350	445	14.00/1.5	475	7,300
20.5-25	20PR	TL/TTF	1,490	520	17.00/2.0	450	9,500
23.5-25	20PR	TL/TTF	1,615	595	19.00/2.5	375	10,900
26.5-25	28PR	TL/TTF	1,743	645	22.00/3.0	475	15,500
29.5-25	28PR	TL/TTF	1,850	750	25.00/3.5	425	17,500
13.00-25	24PR	TL/TTF	1,295	711	8.50	300	2,720
16.00-25	28PR	TL/TTF	1,490	430	11.25/2.0	875	12,700
18.00-25	32PR	TL/TTF	1,615	495	13.00/2.5	850	16,000



## E3/L3 QH812 LOADER TIRE

- ▶ The larger pattern blocks increase the wearability of the tyre
- ▶ Good impacting resistance, strong sludge discharge, anti skid and self-cleaning ability in case of the stagger pattern angle

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
17.5-25	16PR	TL/TTF	1,350	445	14.00/1.5	475	7,300
20.5-25	20PR	TL/TTF	1,490	520	17.00/2.0	450	9,500
23.5-25	20PR	TL/TTF	1,615	595	19.00/2.5	375	10,900
26.5-25	28PR	TL/TTF	1,743	645	22.00/3.0	475	15,500



## L-5 LOADER TIRE

- ▶ This pattern is applicable for more rock operations under severe use conditions such as well lanes and tunnels
- ▶ It has a super-strong tyre body, lengthened tread of tyre and high-strength and high-hardness special tread formula, so that it has good cutting resistance, puncture resistance and wear resistance
- ▶ Due to the special running area and pattern design, the running stability and the passing performance are good

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	INFLATED PRESSURE (kpa)	MAX LOAD (kg)
17.5-25	16PR	TL/TTF	1,340	420	14.00/1.5	475	7,300
20.5-25	20PR	TL/TTF	1,479	500	17.00/2.0	450	9,500
23.5-25	20PR	TL/TTF	1,588	568	19.00/2.5	375	10,900
26.5-25	28PR	TL/TTF	1,758	643	22.00/3.0	475	15,500
29.5-25	28PR	TL/TTF	1,868	718	25.00/3.5	425	17,500

# TRAILER TIRE



# TRAILER TIRE



## QH100 RADIAL TRAILER TIRE

- ▶ Classic radial trailer rib paired with wrap around shoulder tread design provides new levels of stability, durability, and comfort in a radial trailer tire

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	MAX LOAD (LBS)	INFLATED PRESSURE (PSI)
ST175/80R13	6PR	TL	610	177	5.00	1,360	50
ST205/75R14	6PR	TL	664	203	5.50	1,760	50
ST205/75R15	6PR	TL	689	203	5.50	1,820	50
ST225/75R15	8PR	TL	719	223	6.00	3,540	65
ST235/80R16	10PR	TL	782	235	6.50	3,520	80



## QH504 TRAILER TIRE

- ▶ Unique and beautiful pattern, low rolling resistance and good side slipping performance
- ▶ The safety of the trailer tyres running at high speed is improved, and the economic effectiveness is good
- ▶ The trailer tyre is applicable for various trailers

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	MAX LOAD (LBS)	INFLATED PRESSURE (PSI)
7.50-16	10PR	TL	808	220	6.00	2,760	75
ST225/90D16	10PR	TL	808	220	6.00	3,520	75



## QH500 TRAILER TIRE

- ▶ Unique and beautiful pattern, low rolling resistance and good side slipping performance
- ▶ The safety of the trailer tyres running at high speed is improved and the economic effectiveness is good
- ▶ The trailer tyre is applicable for various trailers

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	MAX LOAD (LBS)	INFLATED PRESSURE (PSI)
ST175/80D13	6PR	TL	610	177	5.00	1,360	50
ST205/75D14	6PR	TL	664	203	5.50	1,760	50
ST205/75D15	6PR	TL	689	203	5.50	1,820	50
ST225/75D15	8PR	TL	719	223	6.00	2,540	65



## QH505 TRAILER TIRE

- ▶ Unique and beautiful pattern, low rolling resistance and good side slipping performance
- ▶ The safety of the trailer tyres running at high speed is improved and the economic effectiveness is good
- ▶ The trailer tyre is applicable for various trailers

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	MAX LOAD (LBS)	INFLATED PRESSURE (PSI)
7.00-15	10PR	TL	752	202	5.50	2,340	80
7.50-16	10PR	TL	808	220	6.00	2,760	75
ST205/90D15	10PR	TL	752	202	5.50	2,910	80
ST225/90D16	10PR	TL	808	220	6.00	3,520	75



## QH501 TRAILER TIRE

- ▶ Unique and beautiful pattern, low rolling resistance and good side slipping performance
- ▶ The safety of the trailer tyres running at high speed is improved, and the economic effectiveness is good
- ▶ The trailer tyre is applicable for various trailers

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	MAX LOAD (LBS)	INFLATED PRESSURE (PSI)
ST175/80D13	6PR	TL	610	177	5.00	1,360	50
ST205/75D14	6PR	TL	664	203	5.50	1,760	50
ST205/75D15	6PR	TL	689	203	5.50	1,820	50
ST225/75D15	8PR	TL	719	223	6.00	2,540	65



## QH506 TRAILER TIRE

- ▶ Unique and beautiful pattern, low rolling resistance and good side slipping performance
- ▶ The safety of the trailer tyres running at high speed is improved, and the economic effectiveness is good
- ▶ The trailer tyre is applicable for various trailers

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	MAX LOAD (LBS)	INFLATED PRESSURE (PSI)
ST235/80D16	10PR	TL	782	235	6.50	3,640	80

# TRAILER TIRE

## QH400 MOBILE HOME TIRE



- ▶ The pattern is novel and beautiful, low rolling resistance, good anti-side slip performance
- ▶ High speed driving improves safety performance and has good economic benefits
- ▶ Suitable for all kinds of trailers

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	MAX LOAD (LBS)	INFLATED PRESSURE (PSI)
8-14.5	14PR	TL	707	203	6.00	3,040	115

## QH401 MOBILE HOME TIRE



- ▶ The pattern is novel and beautiful, low rolling resistance, good anti-side slip performance
- ▶ High speed driving improves safety performance and has good economic benefits
- ▶ Suitable for all kinds of trailers

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	MAX LOAD (LBS)	INFLATED PRESSURE (PSI)
6.00-9	10PR	TTF	515	150	4.00	1,375	85

## QH502 BOAT TRAILER TIRE



- ▶ Computer designed tread pattern performance can increase tire durability
- ▶ Smooth tread pattern design to improve trailer drag stability

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	MAX LOAD (LBS)	INFLATED PRESSURE (PSI)
4.80-8	6PR	TL	423	121	3.75	760	90
5.70-8	6PR	TL	469	146	4.50	910	75
4.80-12	6PR	TL	524	121	3.75	990	90
5.30-12	6PR	TL	548	135	4.25	1,050	80



## QH503 BOAT TRAILER TIRE

- ▶ Designed for hard surface utility vehicle applications

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	MAX LOAD (LBS)	INFLATED PRESSURE (PSI)
16.5x6.5-8	6PR	TL	411	165	5.375	785	70
18.5x8.5-8	6PR	TL	462	213	7.00	935	50
20.5x8.0-10	6PR	TL	518	203	6.00	1,100	50

## RG036 BIAS LIGHT TRUCK TIRE



- ▶ Small rotation resistance, flexible turn control
- ▶ Straight pattern with good water drainage, not easy to sideslip

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	MAX LOAD (LBS)	INFLATED PRESSURE (PSI)
11-22.5	14PR	TL	1,054	279	8.25	6,175	100

## RG037 BIAS LIGHT TRUCK TIRE



- ▶ Small rotation resistance, flexible turn control
- ▶ Straight pattern with good water drainage, not easy to sideslip

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	MAX LOAD (LBS)	INFLATED PRESSURE (PSI)
10.00-20	14PR	TTF	1,055	254	7.50	5,730	90

## RG038 BIAS LIGHT TRUCK TIRE



- ▶ Small rotation resistance, flexible turn control
- ▶ Straight pattern with good water drainage, not easy to sideslip

SIZE	PLY	TT/TL	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	STANDARD RIM	MAX LOAD (LBS)	INFLATED PRESSURE (PSI)
11-22.5	14PR	TL	1,054	279	8.25	6,175	100